

**AMENDMENTS THE CLAIMS**

1. (Previously Presented)     An apparatus, comprising:

a current measurement device;

        a head gimbal assembly including a head to at least one of read and write information signals from/to a moving storage medium, said current measurement device electrically coupled to said head and said storage medium; and

        said current measurement device is to measure current between said head and said storage medium wherein said current measurement device is an ammeter/voltage source.

2. (Original) The apparatus of claim 1 wherein said head is a magnetic head/slider.

3. (Previously Presented) An apparatus to measure contact between a magnetic recording head and a storage medium, comprising:

        a current measurement device;

        a head gimbal assembly including a magnetic recording head, said recording head electrically coupled to said current measurement device; and

        a storage medium coupled to said current measurement device; and

        said current measurement device to measure current between said magnetic recording head and said storage medium wherein said current measurement device is an ammeter/voltage source.

4. (Original) The apparatus of claim 3 wherein said storage medium is a rotating magnetic storage disk.
5. (Original) The apparatus of claim 4 wherein said magnetic storage disk is coupled to a spindle and said spindle is coupled to said current measurement device.
6. (Original) The apparatus of claim 5 wherein said current measurement device is a current amplifier.
7. (Cancelled).
8. (Original) The apparatus of claim 7 wherein said ammeter/voltage source is to supply voltage to said magnetic recording head.
9. (Previously Presented) A method of measuring current, comprising:
- coupling a current measurement device to a head of a head gimbal assembly, said head to at least one of read and write information signals from/to a moving storage medium;
  - coupling said current measurement device to a said storage medium; and
  - measuring current between said head and said storage medium with said current measurement device wherein said current measurement device is an ammeter/voltage source.

10. (Original)            The method of claim 9 wherein said head is a magnetic recording head/slider and said storage medium is a magnetic storage disk.

11. (Original)            The method of 10 wherein said magnetic storage disk is coupled to a spindle and said current measurement device is coupled to said spindle.

12. (Original)            The method of claim 11 wherein said current measurement device is a current amplifier.

13. (Cancelled).

14. (Original)            The method of claim 13 further comprising:  
applying voltage to said magnetic recording head with said ammeter/voltage source.

15. (Previously Presented) A method of determining flying height characteristics for a disk drive comprising:

coupling a current measurement device to a head of a head gimbal assembly, said head to at least one of read and write information signals from/to a moving storage medium;

coupling said current measurement device to a said storage medium;

measuring current between said head and said storage medium with said current measurement device; and

determining that said head has too low of a flying height based on said current

measurement wherein said current measurement device is an ammeter/voltage source.

16. (Previously Presented) A method of determining glide height characteristics for a disk drive comprising:

coupling a current measurement device to a glide head of a head gimbal assembly;

coupling said current measurement device to a said storage medium;

measuring current between said head and said storage medium with said current

measurement device; and

determining presence of disk asperities based on said current measurement wherein said current measurement device is an ammeter/voltage source.

17. (Previously Presented) A method of controlling flying height of a magnetic head in a disk drive comprising:

coupling an ammeter/voltage source to the magnetic head of a head gimbal assembly;

coupling said ammeter/voltage source to a rotating magnetic storage medium;

applying voltage to said magnetic head;

measuring current between said head and said storage medium with said ammeter/voltage source; and

adjusting an amount of applied voltage to said magnetic head based on said measure current wherein said current measurement device is an ammeter/voltage source.